



Lo Riser
Model Shown

Drop Deck and Elevating Platform Trailers
both models designed to load/unload at ground level with minimal deck angle
Expedite Deliveries and Increase Operator Safety

Lo Riser Platform/Drop-Deck Trailer

Hydraulic Operated - Ground-Level Loading to Travel Height



4-degree deck angle

transportation height

for FAST & EASY loading/unloading of low ground-clearance equipment and vehicles

NO ramps or lifting

Improve Operator Safety and Reduce Delivery Time



- No beavertail, or crown, creating a hump that could affect (bottom-out) low ground clearance equipment.
- No ramps & No lifting – Hydraulically operated deck gently lowers to ground level to reduce delivery times and improve the safety of both the operator and the equipment.
- Constructed from HSLA (High Strength Low Alloy Steel) for extended trailer life and an improved payload to trailer weight ratio - Increasing load capacity without increasing GVWR.
- A mere 3/16" lip, and a 4-degree angle, easily accommodates any rolling load, even a pallet jack - a task that cannot be done with ramped trailers.
- Unique rubber suspension absorbs the energy from bumps and uneven roads for improved control and a superior ride - Reducing wear on the tow vehicle (and operator), trailer, and payload.
- Ideal for handling scissor lifts, forklifts, floor scrubbers & sweepers, order pickers, pallet jacks, compactors, etc.



Lo Riser Models	Payload Capacity	GVWR	Trailer Weight	Total Length	Deck Length	Deck Width	No. of Wheels
IPT2-312	6,000 lbs.	8,500 lbs.	2,500 lbs.	18' 6"	12' 8"	6' 2"	2
IPT4-516	10,000 lbs.	13,500 lbs.	3,500 lbs.	22' 1"	16'	6' 2"	4
IPT4-616	12,000 lbs.	15,500 lbs.	3,500 lbs.	22' 1"	16'	6' 2"	4
IPT4-716	14,000 lbs.	17,650 lbs.	3,650 lbs.	22' 1"	16'	6' 2"	4
IPT4-816	16,000 lbs.	19,725 lbs.	3,725 lbs.	22' 1"	16'	6' 2"	4

Lift-A-Load Elevating Platform Trailer

Hydraulic Operated - Ground-Level Loading up to 52" Dock Height



Ground & Dock Loading

for Safe, Fast, and Easy equipment deliveries

- Dependable hydraulic system gently lowers deck for ground level loading, and raises the deck to any dock height (up to 52") for fast, easy, and safe equipment unloading and loading.
- Tailgate/Ramp is operated by a winch to eliminate manual lifting and provide load angles between 6.5 and 9.5 degrees.
- Increase operator safety and reduce delivery times.
- Level loading at either ground level or dock height increases safety and avoids equipment damage.
- Trailer deck remains level at all times so payload safely stays in-place until secured for transportation.
- Ideal for handling scissor lifts, forklifts, floor scrubbers & sweepers, order pickers, pallet jacks, compactors, and static loads like safes – To name a few.

EXPEDITE
deliveries and
INCREASE safety

Level loading from the
ground, up to 52" Docks



Lift-A-Load Models	Payload Capacity	GVWR	Trailer Weight	Total Length	Deck Length	Deck Width	Number of Wheels
EPT2-212	4,400 lbs.	7,200 lbs.	2,800 lbs.	22' 3"	12'	5' 10"	2
EPT4-314	7,500 lbs.	11,500 lbs.	4,000 lbs.	24' 6"	14'	5' 8"	4
EPT4-514	10,000 lbs.	14,600 lbs.	4,600 lbs.	24' 6"	14'	5' 8"	4
EPT4-715	15,000 lbs.	21,160 lbs.	6,160 lbs.	25' 8"	15'	5' 2"	4

LIFT-A-LOAD
ELEVATING PLATFORM TRAILERS™

standard features



Adjustable Coupler

4 position coupler/ball hitch accommodates a variety of tow vehicle – Assuring a level trailer.



4-Degree Loading

No crown and a 4-degree loading angle (Lo Riser) allows easy loading of all low-ground clearance, and minimal ramp climbing-capable, equipment – Safely and quickly.



Construction

High Strength Low Alloy Steel (Lo Riser) for durability and assurance that the decking will not bow/sag over time. It also provides the best payload to trailer weight ratio - allowing more load capacity per GVWR.



Suspension System

Unique Rubber Suspension systems absorbs the energy from bumps and uneven roads to provide better control and a smoother ride than conventional trailers. Reducing travel stress on the tow vehicle & operator, trailer, and payload.

optional equipment



Winch

4,000 or 8,000 lb., 12V winch and mount is available to assist loading.



On-Board Power

(battery, charger, and maintainer) eliminates the need for a special connection to the tow vehicle for trailer operation. (Lo Riser Model Shown)



Spare Tire & Mounting Bracket



2 Year Limited Warranty -

New products manufactured by Four Degree Trailer Company, are warranted against defects in materials and workmanship for two (2) years from the date of original purchase, when used as intended under normal operating conditions.

Visit www.fourdegreetrailer.com/warranty for more information.



Four Degree
Trailer Company
3726 US Hwy 34
Kewanee, IL 61443

800-369-5365
info@fourdegreetrailer.com
www.fourdegreetrailer.com

A subsidiary of Rhino Tool Company