

# WEST-MARK

## MILK TANK TRAILER

### Basic Unit Description

Code:	Non-Code 3A Sanitary
Capacity:	6700 Gallons
Shape:	Round, Straight, Cleanbore
Material:	12 Ga Stainless Steel #4 Polish
Design Temp:	165 Degrees F. Max
Products:	Food Grade
Frames:	Stainless Steel Construction
Rings:	Stainless Steel Sections Fully Welded to Shell
Manhole/Gasket:	18" Stainless Steel West-Mark w/ Removable, Cleanable Gasket Around Collar
Venting:	(2) Olsen Vents in Manhole
Spilldam:	Sanitary Stainless Steel Deckplate
Ladder:	Aluminum Tubular, w/ West-Mark Heavy Duty Grated Steps
Insulation:	3" Polystyrene Foam Sheets, Fiberglass at Heads, Urethane Strips at all Rings
Jacketing:	Belly Wrapped 24 Ga Stainless Steel Bright Finish Jacket w/ Lapped Seams, 20 Ga Stainless Steel Heads, Lock Seamed to Jacket
Lights/Wiring:	L.E.D. Per D.O.T. Specifications
Valving:	3" Sanitary Valve at Rear
Upper Fifth Wheel:	5/16" Heavy Duty Upper Fifth Wheel Plate w/ Kingpin, Adjustable in 2" Increments.
CIP:	3 Ball System
Landing Gear:	2-Speed, Steel, Sand Shoes, 50,000 lb. Lift Capacity, Curbside Crank Handle
Bumper:	Stainless Steel Per D.O.T.
Suspension:	Hendrickson AANT 23K
Springs:	Air Ride System
Axles:	23K 5-3/4" Round 71-1/2" Track
Tires:	Various
Wheels:	22.5 x 8.25 Aluminum
Fenders:	Front and Rear Aluminum Contour Fenders w/ Carbon Steel Fender Pipes. Anti-Sail, Anti-Spray Type Mudflaps
Paint:	(1) Color Imron on all Mild Steel Parts



Brochure may reflect some options; additional options available.



RC-02E-01A

P.O. Box 100  
2704 Railroad Avenue  
Ceres, CA 95307

(209) 537-4747  
(800) 692-5844  
Fax (209) 537-1753